

CE

Product Overview

Excel Cat6a cable screened U/FTP PE S-Foil external Grade Fca designed and manufactured to meet and exceed the ISO, CENELEC and TIA standards and supplied on 500m reels. Excel Cat 6A Screened (U/FTP) Cable takes the performance capabilities of copper infrastructure to new levels. This delivers Class EA/ Augmented Category 6 link performance over distances of up 90 metres which supports the applications including 10GBASE-T, 10 Gigabit Ethernet.

Each cable consists of two sets of two pairs are wrapped together in an ""S"" configuration with high quality, strong, aluminium/polyester foil tape providing screening for each pair. The ""S"" Foil configuration ensures separation of the pairs that ensures the performance. The individual pairs are set to different lay lengths to ensure optimum performance.

Product Specifications

Feature	Values
Conductor surface	Bare
Diameter of conductor	0.56 mm
AWG size	23
Conductor category	Class $1 = $ solid
Total number of cores	8
Stranding element	Pairs
Specification core insulation	PE
Core identification	Colour


Excel Solid Cat6A Cable U/FTP S-Foil PE External Grade Fca 500m Black

Item Code: 100-980




Overall screening	None
Conductor screening	Foil
Outer sheath material	PE
Outer sheath colour	Black
Reaction-to-fire class according to EN 13501-6	Fca
Flame retardant	In accordance with EN 60332-1-2 and EN 50399
Outer diameter approx.	6.75 mm
Installation Temperature Range	-1060 °C
Operating Temperature Range	-2060 °C
Category	6A (IEC)

Cross-section diagram



Cable specifications

Features	Values
Dielectric strength	2.5kV for 2s
Maximum pulling load	60N/6.1KgF
MBR during installation	8x cable OD
MBR installed	4x cable OD





Standards

Applicable standard		Subject
ISO/IEC 11801-1:2017		Information technology - Generic cabling for customer premises: Part 1 General Requirements
IEC 61156-5:2020		Multicore and symmetrical pair/quad cables for digital communications - Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz - Horizontal floor wiring - Sectional specification
EN 50173-1:2018		Information technology. Generic cabling systems - General requirements
EN 50173-2:2018		Information technology. Generic cabling systems - Office premises
BS EN 50288-3-1:2013		Multi-element metallic cables used in analogue and digital communication and control. Sectional specification for unscreened cables characterised up to 250 MHz
EN 50399:2011+A1:2016		Common test methods for cables under fire conditions. Heat release and smoke production measurement on cables during flame spread test. Test apparatus, procedures, results
IEC 60332-1-2:2004 + A12	2:2020	Tests on electric and optical fibre cables under fire conditions. Test for vertical flame propagation for a single insulated wire or cable. Procedure for 1 kW pre-mixed flame
ANSI/TIA 568-D:2015		Balanced Twisted-Pair Telecommunications Cabling and Components Standards
IEC 60754-2:2014		Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity
IEC 61034-2:2005+A2:202	20	Measurement of smoke density of cables burning under defined conditions – Part 2: Test procedure and requirements
EN 50575:2014 + A1:2016	5	Power, control and communication cables — Cables for general applications in construction works subject to reaction to fire requirements
RoHS		Compliant to the Restriction of Hazardous Substances
WFD		Compliant to Waste Framework Directive
SCIP		Compliant - Does Not Contain Substances of Concern in Products

Item Code: 100-980



Part Number Table

100-980

Part Number

Description

Excel Cat6A Cable U/FTP S-Foil PE External Grade Fca 500m Black

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.



Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.